



INSULATION:
 EXTERIOR 1ST FLOOR WALLS R13 BLOWN CELULOSE
 BANDS: R13 SPRAY FOAM
 INTERIOR WALLS: R11 FIBERGLASS @ LAUNDRY & BATH WALLS
 GARAGE WALLS @ LIVING SPACE R13 SPRAY
 FOAM.

WINDOW SCHEDULE (◻)

QTY.	SIZE	NOTES	SYMBOL
1	2846		1
1	2630		2
1	2030		3
1	3052 TWIN		4
3	3052		5
1	2040	TEMPERED	6
1	2040 TWIN	TEMPERED	7
1	6/0 SLIDING GLASS DOOR		8
1	4020	TEMPERED	9
1	2020	OCTOGON	10
2	2846 TWIN		11

- 1) ROUGH OPENING ADD 1/4" TO WIDTH & 1/2" TO HEIGHT
- 2) FOLLOW MANUFACTURERS REQUIREMENTS FOR INSTALLING FLASHING
- 3) ALL WINDOWS HAVE UL RATING OF .35 AND SHGC RATING OF .32
- 4) ALL WINDOWS ARE INSULATED WITH LOW 'E'

DOOR SCHEDULE (◻)

QTY.	TYPE	NOTES	RATINGS	SYMBOL
1	16' X 7' GARAGE DOOR	SUNBURST GLASS INSERTS		A
2	3'0" @ PANEL INSULATED STEEL DOOR	1 HR FIRERATED	U<.16 SHGC<.01	B
1	5'4" FULL VIEW PATIO	THERMATRU * w/ GRILLES	U<.33 SHGC<.19	C
1	3'0" FIBERGLASS DOOR	WITH FULL VIEW STORM DOOR	U<.19 SHGC<.01	D
1	16" @ PANEL, HARDBOARD			E
2	2'0" @ PANEL, HARDBOARD			F
1	2'4" @ PANEL, HARDBOARD			G
8	2'6" @ PANEL, HARDBOARD			H
1	5'0" DOUBLE @ PANEL, HARDBOARD			I
1	4'0" DOUBLE @ PANEL, HARDBOARD			J
1	2'8" SCREEN DOOR			K
1	3'0" CASSED OPENING			L
1	5'0" CASSED OPENING			M

NAME	AREA
FIRST FLOOR	946 SF
GARAGE	408 SF
SCREENED PORCH	102 SF
FRONT COVERED PORCH	TT SF

TYPICAL 2X4 SIDING EXTERIOR WALL
 VINYL SIDING
 TYVEK HOUSE WRAP w/ JOINTS TAPED
 1/16" PLYWOOD SHEATHING
 2X4 STUDS @ 16" oc
 BILL SEALER
 BLOWN CELULOSE INSULATION
 1/2" DRYWALL TAPED & SANDED

USE ADVANCED FRAMING TECHNIQUES
 INCLUDING: 2 STUD CORNERS, T WALLS,
 NO HEADERS @ NON BEARING WALLS,
 & A CENTRAL CUTTING AREA.

APPROVED BY: JDO
 2006 IRC & VA USBC
 REVISION DATE: 11-25-08

DRAWN BY: S. HIXON
 SCALE 1/4" = 1'-0"
 NOV 15, 2008



LOT 1 PIEDMONT
 BLACKSBURG, VA 24060

SHEET
 3

1ST FLOOR PLAN